

# MAFI

---



These Austrian-crafted wood floors meet the highest standards of quality and stability.

MAFIs symmetrical 3-layer construction, with matching top and bottom layers, ensures durability—perfect for underfloor heating. Made with natural adhesives and finished in linseed oil, they feature an open-pore surface for a healthier indoor environment. Easy to clean with soap and water, they're the ideal choice for those seeking a truly natural interior.

# Oak

---



Extreme White



White



Grey



Volcano Grey



Graphite



Natural



Riva Mezzo



Volcano I



Riva Mare



Volcano II



Volcano III

## Planks from: £139 sqm

Widths available: 160mm, 190mm, 245mm, 260mm, 280mm, 300mm

Thickness available: 16 and 19mm

3 layer engineered

## Herringbone & Chevron: From £154 sqm

Herringbone 160mm x 580mm, , 190mm x 780mm, 245mm x 980mm

Chevron 160mm x 580mm, 160mm x 600mm, 190mm x 580mm, 190mm x 600mm

Thickness available: 16 and 19mm

3 layer engineered

Not all colours available as Herringbone & Chevron.

Prices do not include VAT or delivery

# Other Species

---



White Ash



White Fir



Ash Volcano



Larch End Grain



Black Walnut Oiled

## Planks from: £114 sqm

Widths available: 155mm, 185mm, 200mm, 220mm, 240mm, 260mm, 280mm, 300mm

Thickness available: 16 and 19mm

3 layer engineered

## Herringbone & Chevron: From £184 sqm

Herringbone 155mm x 580/780mm, , 185mm x 580/780mm

Chevron 155mm x 540/730mm, 155mm x 550/740mm, 185mm x 710mm, 185mm x 550/740mm,

Thickness available: 16 and 19mm

3 layer engineered

Not all species available as Herringbone & Chevron.

Prices do not include VAT or delivery

## Technical Specifications

<b>SPECIES</b>	European oak & other species
<b>CERTIFICATION</b>	<b>Upon Request</b>
<b>APPLICATION</b>	Commercial and residential (Indoor)
<b>CONSTRUCTION</b>	3 Layer engineered: 4mm top and bottom layer oak with 8 or 11mm softwood core
<b>BEVEL</b>	Micro bevel as standard
<b>INSTALLATION TECHNIQUE</b>	Nail, glue bonding or floating
<b>SUITABLE FOR UFH</b>	Yes
<b>FIRE CLASSIFICATION</b>	EN: 13501: Dfl-S1
<b>THERMAL CONDUCTIVITY</b>	0.119-0.17 $\lambda$ W/mK
<b>HARDNESS</b>	Oak: 4,982 N (Janka). Other Species available on request

Timber floors are easy to care for, please call us for further information on the best way to look after your floor.

Timber is a living material. A wooden floor, although no longer growing as part of a tree, is still very much part of its environment. As such, it responds to the light, temperature, humidity and wear to which it is exposed.

As the floor ages the colour of the wood will mellow and change. This is a natural process that occurs as the surface of the wood is exposed to oxygen in the air and to ultraviolet light from the sun. Painted surfaces, upholstery, furniture and rugs all undergo this same process over time.

After a number of years you may wish to have the floor surface sanded down and re-finished. You could then choose to re-oil the floor or have it stained first or even re-finished in lacquer.



West:  
61 Paddington St  
London W1U 4JD  
020 7486 4838

East:  
7a Ezra Street  
London E2 7RH  
020 7221 8188

Registered in England & Wales: Solid Floor Ltd. 7a Ezra Street, London E2 7RH  
Company Reg No: 03287805 | VAT Reg No: 710 4793 50  
FSC® licence: C117337 | FSC COC: CU-COC-828136 | PEFC COC: CU-PEFC-828136  
solidfloor.co.uk sales@solidfloor.co.uk  solidfloor  solidfloor