

Tate Bute Herringbone Sale Special



Tate is defined by visible horizontal rough sawn marks, providing character and texture which results in a very forgiving floor. These distinctive oak floors give a strong foundation to the most eclectic schemes and are popular amongst our architects and designer clientele.

Bute - the best-seller within the range, is a mid-toned very versatile light grey-brown floor which suits modern schemes as well as more traditional interiors.

Herringbone: £89 sqm

Baton size: 15mm x 145mm x 580mm

Duplex engineered

Rustic Mix grade with filled knots up to 60mm allowed, micro bevel edge.

Price does not include VAT or delivery

Technical Specifications

SPECIES	European oak
APPLICATION	Commercial and residential (Indoor)
CONSTRUCTION	Duplex engineered 4mm top layer oak
BEVEL	Micro bevel as standard
INSTALLATION TECHNIQUE	Nail, glue bonding or floating
SUITABLE FOR UFH	Yes, when duplex engineered
FIRE CLASSIFICATION	EN: 13501: Dfl-S1
THERMAL CONDUCTIVITY	0.119-0.17 λ W/mK
HARDNESS	4,982 N (Janka)

Timber floors are easy to care for, please call us for further information on the best way to look after your floor.

Timber is a living material. A wooden floor, although no longer growing as part of a tree, is still very much part of its environment. As such, it responds to the light, temperature, humidity and wear to which it is exposed.

As the floor ages the colour of the wood will mellow and change. This is a natural process that occurs as the surface of the wood is exposed to oxygen in the air and to ultraviolet light from the sun. Painted surfaces, upholstery, furniture and rugs all undergo this same process over time.

After a number of years you may wish to have the floor surface sanded down and re-finished. You could then choose to re-oil the floor or have it stained first or even re-finished in lacquer.